Technical Information Sheet



extra Wallpaper Adhesive Super Economy Pack Tapetenkleister extra Super-Sparpack

Instructions for use: The adhesive is suitable for pasting light to heavy weight paper wallpapers on

plaster, concrete, gypsum and plasterboards. Particularly suited for rough sur-

faces.

Technical specifications: Components: starch ether, rheological additive

Density: approx. 0.4 g/cm³

pH-value: approx. 8

Solubility: ready for use after approx. 30 minutes

Usage: approx. 200 ml/m²

Surface preparation: The surface must be dry, firm and free of dust and grease. Remove old, peeling

wallpapers and distemper paints using *PUFAS Wallpaper Remover*. Make good cracks and holes using *PUFAS Interior* or *PUFAMUR Super Bonding Filler*.

Pre-treat strongly absorbent, abrasive and chalky surfaces with *PUFAS Deeply-Penetrating Primer – solvent free*. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using

PUFAS Insulating Spray White.

Application: Stirring vigorously, sprinkle extra Wallpaper Adhesive into clean, cold water

(see table) and continue to stir for a few minutes. Leave for approx. 30 minutes

and then stir vigorously again.

Evenly apply the adhesive to the wallpaper using a brush. Fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpa-

per manufacturer's instructions for use.

We recommend to add 750 g PUFAS Wallpaper and Border Adhesive per 3-4 litres mixed extra Wallpaper Adhesive for use on hardly absorbent surfaces and

to increase the moisture resistance.

Do not use if the surface and room temperature are below + 5° Celsius!

Remove adhesive residues using a damp cloth.

Clean tools in water after use.

Mixing ratio for 500 g packet:

for	Mixing ratio	Quantity of water per 500-g packet	Coverage of a 500-g packet
Pre-pasting	1:25	12,5 l	Approx. 70 m ²
Light weight wallpapers	1:20	10 l	50-60 m ²
Woodchip wallpaper	1:15	7.5 l	35-40 m ²
Heavy wallpapers	1:10-1:12	5-6 I	25-30 m ²

Mixing ratio for 1 kg packet:

for	Mixing ratio	Quantity of water per 1 kg packet	Coverage of a 1 kg packet
Pre-pasting	1:25	25 I	Approx. 140 m ²
Light weight wallpapers	1:20	20	100-120 m ²
Woodchip wallpaper	1:15	15 I	70-80 m²
Heavy wallpapers	1:10-1:12	10-12 l	50-60 m ²

Storage: Store in a cool and dry place!

Available sizes: 500 g collapsible box 002511000

1 kg collapsible box 002512000