

## extra Special Wallpaper Adhesive Super Economy Pack Spezial-Kleister extra Super-Sparpack

Instructions for use: extra Special Wallpaper Adhesive is suitable for pasting woodchip wallpapers,

paper wallpapers, vinyl wallpapers and similar wall coverings on plaster, concrete, gypsum and plasterboards. Particularly suited for rough surfaces.

**Technical specifications:** Components: starch ether, rheological additive

> Density: approx. 0.4 g/cm3

pH-value: approx. 8

Solubility: ready for use after approx. 30 minutes

Usage: approx. 200 ml/m<sup>2</sup>

Surface preparation: The surface must be dry, firm and free of dust and grease. Remove old, peeling

wallpapers and distemper paints using PUFAS Wallpaper Remover. Make good cracks and holes using PUFAS Interior or PUFAMUR Super Bonding Filler.

Pre-treat strongly absorbent, abrasive and chalky surfaces with PUFAS Deeply-Penetrating Primer - solvent free. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using

PUFAS Insulating Spray White.

Application: Stirring vigorously, sprinkle extra Special Wallpaper Adhesive into clean, cold

water (see table) and continue to stir for a few minutes. Leave for approx. 30

minutes and then stir vigorously again.

Evenly apply the adhesive to the wallpaper using a brush. Fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpa-

per manufacturer's instructions for use.

We recommend to add 750 g PUFAS Wallpaper and Border Adhesive per 3-4 litres mixed extra Special Wallpaper Adhesive for use on hardly absorbent sur-

faces and to increase the moisture resistance.

Do not use if the surface and room temperature are below + 5° Celsius!

Remove adhesive residues using a damp cloth.

Clean tools in water after use.

Mixing ratio for 500 g packet:

for	Mixing ratio	Quantity of water per 500 g packet	Coverage of a 500 g packet
Pre-pasting	1:20	10	Approx. 70 m <sup>2</sup>
Light weight wallpapers	1:16	81	40-45 m <sup>2</sup>
Woodchip wallpaper	1:14	7	35-40 m <sup>2</sup>
Vinyl + embossed wallpaper	1:12	61	30-35 m <sup>2</sup>
Heavy wallpapers	1:12	61	30-35 m <sup>2</sup>

Mixing ratio for 1 kg packet:

for	Mixing ratio	Quantity of water per 1 kg packet	Coverage of a 1 kg packet
Pre-pasting	1:20	20	Approx. 140 m <sup>2</sup>
Light weight wallpapers	1:16	16 I	80-85 m²
Woodchip wallpaper	1:14	14	70-75 m²
Vinyl + embossed wallpaper	1:12	12 l	60-65 m²
Heavy wallpapers	1:12	12	60-65 m²

Storage: Store in a cool and dry place!

Available sizes: 500 g collapsible box 002501000

> 1 kg collapsible box 002502000