

## Wallpaper paste

### Instructions for use:

*Wallpaper paste* is suitable for all dry-strippable wallpapers as non-woven wallpapers and all similar wall coverings.

### Technical specifications:

Components: modified starch, resin powder, Methylcellulose, additives  
Density: approx. 0.50 g/cm<sup>3</sup>  
pH-value: approx. 9  
Solubility: Ready for use after approx. 30 minutes  
Usage: approx. 200 ml/m<sup>2</sup>

### Surface preparation:

The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using *PUFAS Wallpaper Remover*. Make good cracks and holes using *Fill&Finish Interior* or *pufamur Super Bonding Filler*. Pre-treat highly absorbent, sanding and chalking surfaces using *PUFAS Deeply Penetrating Primer - Solvent Free*. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *decotric Insulating Spray*. We recommend a first coat with *Pufas Wallpaper Primer – Easy strip-off WG white* if hanging highly translucent wallpapers and where surfaces are highly contrasting.

### Application:

Stirring vigorously, sprinkle *Wallpaper paste* into clean, cold water and continue to stir for a few minutes. Leave for approx. 30 minutes and then stir vigorously again.

#### Applying to wallpaper:

Evenly coat the wallpaper with *Wallpaper paste* and fold the pasted ends together. After leaving to soften for sufficient time, hang the wallpaper with matching seams and press down.

#### Applying to the surface:

Use a lambs wool roller to evenly apply the mixed *Wallpaper paste* to the surface over a width of 1-2 wallpaper widths. Place the wallpaper strip directly into the fresh adhesive bed and uniformly press down.

Always follow the wallpaper manufacturer's instructions for use.

Please consult safety data sheet for safety-relevant data.

Do not use if the surface and room temperature are below + 5° Celsius!

Remove adhesive residues using a damp cloth.

Clean tools in water after use.

### Mixing ratio:

for	Mixing ratio	Quantity of water per 200-g packet	Coverage of a 200-g packet
Pre-pasting	1:40	8 l	60-80 m <sup>2</sup>
Non woven wallpapers – for applying onto the wall or to the wallpaper	1:20	4 l	20-25 m <sup>2</sup>

### Storage:

Store in a cool and dry place!

### Available size:

Article no 000501999 100 g

### Minimum durability:

5 years as of date of manufacture

### Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.